



Combi-inspectieputten D-RWA

Chambres de visite "combi"

Basiselement / Élément de base

Aansluiting Raccord di (mm)		Inw. Afm. Section int. di (mm)	Inw. Hoogte Hauteur int. (mm)	Wanddikte Paroi (mm)	DWA-stroomprofiel met afsluitklep	Rubbering Joint
DWA	RWA					
150	400-800	1000	2500	150	x	x
200	400-800	1000	2500	150	x	x
250	400-800	1000	2500	150	x	x
300	400-800	1000	2500	150	x	x
400	400-800	1000	2500	150-255	x	x
500	400-800	1000	2500	150-255	x	x
600	400-800	1000	2500	150-325	x	x

Schachtelement / Élément de fût

Inw. Afm. Section int. di (mm)	Inw. Hoogte Hauteur int. (mm)	Wanddikte Paroi (mm)	Rubbering Joint
1000	500	150	x
1000	1000	150	x
1000	1500	150	x
1000	2000	150	x
1000	2500	150	x

Schachtelement met vaste dekplaat / Élément de fût avec la dalle de couverture solidaire

Inw. Afm. Section int. di (mm)	Inw. Hoogte Hauteur int. (mm)	Wanddikte Paroi (mm)	Rubbering Joint
1000	500	150	x
1000	1000	150	
1000	1500	150	
1000	2000	150	x
1000	2500	150	x

Dekplaat / Dalle de couverture

Inw. Afm. Section int. di (mm)	Uitw. Afm. Section ext. (mm)	Mangat Trou-homme (mm)	Wanddikte Paroi (mm)
1000	1300	700	150
1000	1300	GY Ø700	150
1000	1300	/	150